



21-45-605.4-1-
 OUT OF 605.4-1-
 NOTE* 605.4-1-21.30
 41-X-42 / 4-

REVISED
 Added lots 31 and
 32, Phase 2
 DATE
 4/24/2000

Line	Bearing	Distance
L1	N 69° 44' 16" E	23.64'
L2	N 56° 09' 41" E	60.64'
L3	S 45° 57' 37" W	74.00'
L4	S 55° 02' 44" W	32.82'
L5	S 19° 14' 16" E	88.64'

Curve	Radius	Chord Bearing and Distance
C1	50.00'	N 57° 33' 40" E 51.1'
C2	40.00'	N 49° 43' 47" E 31.1'
C3	50.00'	S 62° 25' 23" E 48.1'
C4	50.00'	S 14° 23' 13" W 74.1'
C5	40.00'	N 83° 05' 53" W 32.1'
C6	50.00'	N 81° 08' 48" W 33.1'
C7	190.00'	S 64° 09' 10" W 58.1'
C8	90.00'	S 36° 00' 06" W 31.1'
C9	190.00'	S 50° 39' 13" W 31.1'
C10	134.00'	S 40° 32' 39" W 67.1'
C11	134.00'	N 46° 35' 41" W 73.1'
C12	134.00'	N 85° 02' 16" W 102.1'
C13	134.00'	S 53° 45' 19" W 85.1'
C14	134.00'	S 23° 46' 35" W 52.1'
C15	40.00'	S 35° 40' 23" W 31.1'
C16	50.00'	S 19° 24' 49" W 63.1'
C17	50.00'	S 44° 03' 21" E 40.1'